

21.5" 23.6" FHD Touch CCTV Monitor

AUSPICE STAR



LED technology benefits from intelligent color corrective technology with a mercury-free WLED backlight that automatically detects image signal and controls backlight brightness for blacker blackspurer whites and more clearly

Features

- FHD display 1920 x 1080
- Resistive touch panel
- Excellent contrast ratio and brightness
- Built-in 3D comb-filter & 3D de-interlace
- VESA hole 100 x 100 (mm)
- PIP / PBP Multi-display function
- 2 x Composite BNC In / Out for looping
- Remote supported
- No Mercury. Enviroment-friendly Product
- LED backlit leads to less power consumption



| Model | A215M6-LED (RT) | A236M16-D17 (RT) |
|--|--|--------------------|
| General | | |
| Diagonal size | 21.5" | 23.6" |
| Panel type | TFT LCD | TFT LCD |
| Aspect ratio | 16:9 | 16:9 |
| Number of pixels | 1920 x 1080 | 1920 x 1080 |
| Pixel pitch | 0.24825 x 0.24825 mm | 0.2715 x 0.2715 mm |
| Color depth | 16.7 Million Colors | |
| Backlight | LED | LED |
| Touch Type | Five - Wire Analogue Resistive | |
| Touch Interface | USB | |
| Optical (typ.) | | |
| Brightness | 300 cd/m2 | 300 cd/m2 |
| Contrast ratio | 10000:1 | 10000:1 |
| Response time (Tr + Tf) | 5 ms | 5 ms |
| Viewing angle | Vertical -85°~85° / Horizontal -80°~80° | |
| Operation | | |
| Input Interface | BNC x 2, HDMI x 1, VGA x 1 | |
| Output Interface | BNC x 2 | |
| Display mode | Video 1 / Video 2 / HDMI / VGA | |
| OSD | Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Color Temp, DNR | |
| OSD Languages | English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech | |
| Speaker | 1.5 W x 2 | |
| Remote control | Yes | |
| Composite Video | | |
| System | | |
| Video processing | PAL / NTSC | |
| Electrical | Motion Adaptive 3D De-Interlacer and DNR, 4H Comb filter Y/C separation | |
| AC power | | |
| AC power | AC 100-240V 50/60HZ | |
| Power consumption | < 33W | <36W |
| Power supply | External power adapter | |
| Mechanical | | |
| Case material | | |
| Case material | Metal | |
| Dimension (W x H x D) (include stand) | 501 x 307 x 41 mm | 550 x 350 x 49 mm |
| Support | | |
| Support | Frame Type | |
| Mounting interface | 100 x 100 mm , M4 x 4 holes | |
| Net weight (Monitor & stand) | 5.8Kgs (12.8 lbs) | 6.4Kgs (14.1 lbs) |
| Environment | | |
| Temperature | Operation: 0°~40°C(32°~104°F) , Storage: -10°~60°C(14°~140°F) | |
| Humidity | 10%-90% | |
| Safety | FCC, CE, ROHS | |
| Delivery set | Monitor, Power cord with adapter, VGA cable, Remote controller, USB Cable, User Manual | |

** Design and specs are subjective to change without notice

