



## Features

- 23.4" FHD LED Flat Panel: 1920 x 1080
- Capacitive touch panel
- 10 fingers touch
- Excellent contrast ratio and brightness
- LED backlit leads to lower power consumption
- With HDMI / DVI / VGA video inputs.
- USB 3.0 for storage device.

## A240M6 - PCT 10 fingers Touch Display

The Auspice Star A240M6-LED is the perfect solution for both commercial and consumer touch screen applications. With an intuitive multi-touch LED display and full HD resolution, the A240M6-LED delivers a versatile touch solution for use as a POS display, information kiosk, or in hospital and classroom environments. Equipped with 1920x1080 Full HD resolution, and 5000 : 1 Contrast Ratio, the Auspice Star A240M6-LED delivers extremely sharp and crisp images. HDMI, VGA, and DVI inputs provide flexible and convenient connectivity, while a VESA-mountable design offers additional convenience for use as a wall-mounted display.

Model	A240M6-LED
<b>General</b>	
Diagonal size	24"
Panel type	MVA
Aspect ratio	16:9
Number of pixels	1920 x 1080
Pixel pitch	0.27675x0.27675mm
Color depth	8-bit
Backlight	LED
<b>Touch specifications</b>	
Touch type	Projected Capacitive Multi-Touch Panel
Touch Point	PCT 10 fingers
Interface	USB
<b>Optical (typ.)</b>	
Brightness	250 cd/m <sup>2</sup>
Contrast ratio	5000:1
Response time ( Tr + Tf)	12 ms
Viewing angle	Vertical -89°~89° / Horizontal -89°~89°
<b>Operation</b>	
Input Interface	VGA+DVI+HDMI+Audio+USB 3.0(1up/2down)
OSD Languages	English, German, Spanish, French, Italian, Russian
Speaker	3W x 2
Remote control	NO
<b>Electrical</b>	
AC power	AC 100-240V 50/60HZ
Power consumption	Normal < 30W (w/o USB device) Power Saving < 0.5W
Power supply	50W/12V adapter
<b>Mechanical</b>	
Case material	F/C: ABS, B/C: ABS
Color	Black/Silver
Dimensions ( W x H x D)	585 mm x 429 mm x 49 mm
Support	Frame type
Mounting interface	75 x 75 mm , 100x 100 mm
Net weight	6.08Kgs(13.4 lbs)
<b>Environment</b>	
Temperature	5°C to 35°C
Humidity	20% to 90% non-condensing
<b>Standards</b>	
Safety	CE, FCC