



HDMI / VGA / PC Audio / RCA x 2 / BNC In x 2 / BNC Out x 2 / HDMI x 1

### SPECIAL FEATURES

▶ 3D comb filter high quality motion adaptive

3D comb filter clearly differentiates luminance signal and chrominance signal and effectively reduce flickering and noise. Therefore ensures clear contour line of image.

▶ 3D De-interlace

▶ 3D decoder

▶ 3D noise reduction

▶ V&H adjustable

▶ User friendly OSD interface

OSD adopts user friendly graphic interface and supports 11 languages. It is easily to set up by front panel control buttons and remote controller.

▶ Looping function

2 BNC inputs and 2 BNC outputs

### Remote Controller



### Specification

CCTV LCD SERIES	A26M1-LCD
<b>Display</b>	
Screen Size	26"
Max Resolution	FULL HD 1920x1200 620 TV Lines
Brightness	400cd/m <sup>2</sup>
Pixel Type	Active Matrix TFT
Pixel Pitch	0.2865(H) x 0.2865(V)
Display Color	16.7 Million
Backlit	CCFL
Contrast Ratio	1000:1
Aspect Ratio	16:10
Viewing Angle (H/V)	160° / 160°
Response Time	5ms
Video System	NTSC/PAL
<b>Interface</b>	
Video In/Out (BNC Type)	2/2
VGA In/Out (15Pin D-Sub)	1
HDMI In	1
Video Audio (2 channels RCA input)	YES
Audio Input PC Audio	1
<b>Audio</b>	
Built In speaker	Yes (1.5W x 2)
<b>Special Features</b>	
3D Comb Filter	YES
3D De-Interlace	YES
Multi-Language	English · German · French · Italian · Spanish · Russia · Turkish · Japanese · Polish
Key Lock Function	YES
<b>Dimension</b>	
Net (WxHxD)	587x390x99[mm]
Weight	N.W.: 8.8kgs G.W.: 11.3kgs
<b>Environmental Conditions</b>	
Operating Temperature	32° to 104° F (0° to 40° C)
Storage temperature	14° to 140° F (-10° to 60° C)
Operating Humidity	10% to 90% relative, non-condensing
<b>Cabinet</b>	
Finish/Tilt Stand	Black/Yes
<b>Mount</b>	
Vesa Mounts Size	200 x 100 (mm)
<b>Power</b>	
Electrical Ratings	AC100~240 【 50 / 60 】
Consumption < On	100W Max
Regulations	FCC-DOC, CE, ROHS

\* Design and Specs are subject to change without any notice

### Dimensions

