

26" FHD CCTV Monitor

AUSPICE STAR



- FHD display 1920 x 1080
- HDMI / BNC / VGA all ports in one monitor
- Analogue video is very clear with no detail loss
- Built-in 3D comb-filter & 3D de-interlace
- Rugged metal case
- VESA hole 200 x 100 (mm)
- PIP / PBP Multi-display function
- 2 x Composite BNC In / Out for looping
- Longevity: design to run 24 / 7 / 365

Input / output



Model	A26M1-4D
General	
Diagonal size	26"
Panel type	TFT LCD
Aspect ratio	16:10
Number of pixels	1920 x 1200
Pixel pitch	0.2865 x 0.2865 mm
Color depth	16.7 Million Colors
Backlight	CCFL
Optical (typ.)	
Brightness	400 cd/m2
Contrast ratio	1000:1
Response time (Tr + Tf)	5 ms
Viewing angle	Vertical -80°~80° / Horizontal -80°~80°
Operation	
Input Interface	BNC x 2, HDMI x 1, VGA x 1
Output Interface	BNC x 2
Display mode	Video 1 / PC / HDMI / SDI
OSD	Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Color Temp, DNR
OSD Languages	English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech
Speaker	1.5 W x 2
Remote control	YES
Composite Video	
System	PAL / NTSC
Video processing	Motion Adaptive 3D De-Interlacer and DNR, 4H Comb filter Y/C separation
Electrical	
AC power	AC 100-240V 50/60HZ
Power consumption	< 100W
Power supply	AC power cord
Mechanical	
Case material	Metal
Dimension (W x H x D) (include stand)	587 x 390 x 99 mm
Mounting interface	200 x 100 mm
Net weight (Monitor Only)	8.8Kgs (19.4 lbs)
Environment	
Temperature	Operation: 0°~40°C(32° ~104°F) , Storage: -10°~60°C(14° ~140°F)
Humidity	10%-90%
Safety	FCC, CE, ROHS
Delivery set	Monitor, Power cord, VGA cable, User Manual, Remote controller

** Design and specs are subjective to change without notice