

32"40" FHD CCTV Monitor

Auspice STAR



Features

- Full HD (FHD) display (1080i/p)
- Rugged Metal case
- Excellent contrast ratio and brightness
- Built-in 3D comb-filter & 3D de-interlace
- Remote supported
- PIP / PBP Multi-display function
- HDMI / BNC / VGA all ports in one monitor.

Input / output



Model	A320M1-LED	A4001-LED
General		
Diagonal size	17"	19"
Panel type	TFT LCD	TFT LCD
Aspect ratio	16:9	16:9
Number of pixels	1920 x 1080	1920 x 1080
Pixel pitch	0.36375 x 0.36375 mm	0.2865 x 0.2865 mm
Color depth	16.7 Million Colors	
Backlight	LED	LED
Optical (typ.)		
Brightness	400 cd/m ²	400 cd/m ²
Contrast ratio	5000:1	3500:1
Response time (Tr + Tf)	8.5 ms	6.5 ms
Viewing angle	Vertical -88°~88° / Horizontal -88°~88°	
Operation		
Input Interface	BNC x 2, HDMI x 1, VGA x 1	
Output Interface	BNC x 2	
Display mode	Video 1 / Video 2 / PC / HDMI	
OSD	Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Color Temp, DNR	
OSD Languages	English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech	
Speaker	1.5 W x 2	
Remote control	YES	
Composite Video		
System	PAL / NTSC	
Video processing	Motion Adaptive 3D De-Interlacer and DNR, 4H Comb filter Y/C separation	
Electrical		
AC power	AC 100-240V 50/60HZ	
Power consumption	< 70W	< 85W
Power supply	AC Power Cord	
Mechanical		
Case material	Metal	
Dimension (W x H x D) (include stand)	747 x 450 x 80 mm	884.5 x 525 x 69.2 mm
Mounting interface	200 x 100 mm	400 x 200mm
Net weight (Monitor & stand)	11.8Kgs (26.01 lbs)	20Kgs (44.1 lbs)
Environment		
Temperature	Operation: 0°~40°C(32° ~104°F) , Storage: -10°~60°C(14° ~140°F)	
Humidity	10%~90%	
Safety	FCC, CE, ROHS	
Delivery set	Monitor, Power cord , VGA cable, Remote User Manual	

** Design and specs are subjective to change without notice