

55"

FHD CCTV Monitor



Auspice Star

Features

- Full HD (FHD) display (1080i/p)
- Wide viewing angle (89/89/89/89)
- Excellent contrast ratio and brightness
- Built-in 3D comb-filter & 3D de-interlace
- VESA hole 400 x 400 (mm)
- PIP / PBP Multi-display function
- HDMI / BNC / VGA all ports in one monitor.



Model	A550C2-LED
General	
Diagonal size	55"
Panel type	TFT LCD
Aspect ratio	16:9
Number of pixels	1920x1080
Pixel pitch	0.21 x 0.63 mm
Color depth	16.7 Million Colors
Backlight	LED
Optical (typ.)	
Brightness	360 cd/m2
Contrast ratio	4000:1
Response time (Tr + Tf)	8 ms
Viewing angle	Vertical -89°~89° / Horizontal -89°~89°
Operation	
Input Interface	BNC x 2, HDMI x 1, VGA x 1
Output Interface	BNC x 2
Display mode	Video 1 / Video 2 / PC / HDMI
OSD	Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Color Temp, DNR
OSD Languages	English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech
Speaker	8 W x 4
Remote control	YES
Composite Video	
System	PAL / NTSC
Video processing	Motion Adaptive 3D De-Interlacer and DNR, 4H Comb filter Y/C separation
Electrical	
AC power	AC 100-240V 50/60HZ
Power consumption	< 155 W
Power supply	AC power cord
Mechanical	
Case material	Plastic
Dimension (W x H x D) (include stand)	1256 x 802 x 280 mm
Mounting interface	400 x 400 mm
Net weight	29Kgs (63.9 lbs)
Environment	
Temperature	Operation: 0°~40°C(32°~104°F) , Storage: -10°~60°C(14°~140°F)
Humidity	10%-90%
Safety	FCC, CE, ROHS
Delivery set	Monitor, Power cord, VGA cable, User Manual, Remote controller

** Design and specs are subjective to change without notice

Auspice Star

Company address: 2F., No.330, Datong Rd., Gueishan Township, Taoyuan City, Taoyuan County 33352, Taiwan, R.O.C.

Tel: +886-3-350-1555 Fax: +886-3-350-1388