

# 8" Test Monitor

Auspice STAR



## Descriptions

This small screen monitor is one of our most adaptable models for use in security surveillance and in a corporate AV environment where the space is limited. Applied LED backlight – brighter picture using less power IR remote control Rechargeable battery pack available for mobility

## Features

- 8" LCD Monitor
- BNC Video Input
- IR Remote control
- Video / NTSC auto switch
- Application: CCTV Testing and monitoring
- LED backlight – brighter picture using less power
- Rechargeable battery pack available for mobility

Model	ASR80
<b>General</b>	
Diagonal size	8"
Panel type	TFT LCD
Aspect ratio	4:3
Number of pixels	800 x 600
Pixel pitch	0.0675 x 0.2025 mm
Color depth	262114
Backlight	LED
Optical (typ.)	
Brightness	350 cd/m2
Contrast ratio	400:1
Response time ( Tr + Tf)	12ms
Viewing angle	Vertical -90°~70° / Horizontal -85°~85°
<b>Operation</b>	
Input Interface	BNC x 1, VGA x 1, PC Audio x 1
Display mode	AV / VGA
OSD	Contrast, Brightness, Color Temp
OSD Languages	English
Remote control	Yes
<b>Composite Video</b>	
System	PAL / NTSC
<b>Electrical</b>	
Power	DC12V
Power consumption	< 10W
Power supply	External power adapter
<b>Mechanical</b>	
Case material	Plastic ( Black )
Dimension ( W x H x D ) (include stand)	205 x 236 x 106 mm
Support	Pedestal base
Net weight (Monitor & stand)	0.7kgs ( 1.5 lbs )
<b>Environment</b>	
Temperature	Operation: 0°~40°C(32°~104°F) , Storage: -10°~60°C(14°~140°F)
Humidity	10%~90%
Safety	FCC, CE, ROHS
Delivery set	
Accessory	Power Cord with adapter, Video cable, Car charger, Remote, VGA cable, manual



\*\* Design and specs are subjective to change without notice