Auspice Star Co.Ltd       古鑫國際科技股份有限公司       Company address: 2F.,No.330,Datong Rd.,Gueishan Township,Taoyuan County 33352,Taiwan(R.O.C)       TEL: 886-3-3501555 , FAX : 886-3-3501388       Web Site : www.auspicestar.com , E-mail : info@auspicestar.com	
LED	CCTV MONITOR
	Suitable for Test monitor & Car use     PAL / NTSC auto detection     Easy to carry it outside and doing test after installation.     Mirror Function.     Two signal input (Video 1 / Video 2)     Built-in Speaker.
CCTV LED SERIES Display	Battery support.  ASR-56
Screen Size Max Resolution Brightness	5.6 " 960 x 234 200 cd/m2
Pixel Type Pixel Pitch Display Color Backlight	Active Matrix TFT 0.118 (H) x 0.362 (V) 16.7 Million LED
Aspect Ratio Video System Interface	4 : 3 NTSC/PAL auto detection
Video In/Out (BNC Type) Audio In/Out (RCA Type) Audio Built In speaker	2 (Cable connection type) 1/1 (Cable connection type) YES
Special Features Mirror Function Multi-Language	YES English / Chinese
Dimension Net (WxHxD) Cabinet Finish/Tilt Stand	155 x 105 x 25 Black/Yes
Power Voltage Input Operation Temperature	10 to 36V DC
Operation Temperature Accessories	- 10 ~ + 70 degree C Adapter , RCA cable , user manual , Monitor stand
Interface	BNC & RCA Cable     1   2     1   2     2   4     5   Audio 1 (White RCA Jack )     5. Audio 2 (Red RCA Jack )     * The specifications are subject to change without notice.

\* Design and Specs are subject to change without any notice